

Sturdy. Green. Energy-Efficient.





vanEE is extending its Energy Efficient unit selection under a new family name: the Silver Series.

Now meets the highest standards of efficient home programs!

These new products are specially designed to deliver more benefits to efficient home builders. In addition to providing high performances, this series offers eco-efficient ventilation.

- With an exceptional sensible recovery efficiency of 75% SRE @ 0°C and 70% SRE @ -25°C, these units allow reaching builder option package points required to obtain energy efficient program certification
- Equipped with 2 powerful and reliable motors providing best in class fan efficacy
- Quick installation with airflow balancing system
- Can comply with highest requirements of efficient home programs such as Novoclimat 2.0 and ENERGY STAR®
- 5-year warranty





Quick and Easy Strap System

Duct mounting straps eliminate the need to seal with tape and protect the vapor barrier for quicker installations and easy maintenance.

HomeShield™ Defrosting System

Prevents ice build-up on recovery module without creating negative indoor air pressure.

Motor Assembly

Can easily be replaced in less than 7 minutes, allowing a simple and fast maintenance.

Balancing System

Pressure taps eliminate the need for an external flow meter and reduce installation time.

Heat Recovery Core (HRV)

Offers superior efficiency by warming the incoming fresh, colder air in winter before it is distributed throughout your home.

OR

Energy Recovery Core (ERV)

Recovers heat and recuperates the energy trapped in moisture, which greatly improves the overall recovery efficiency.




Easy to Reach Filters

Washable foam filters effectively filter airborne particles, such as pet dander, lint, dust and mold spores, while protecting the equipment from dust build-up.

NEW

NEW



Specifications	60H-V+	90H-V+	90H-V ECM HRV	90H-V ECM ERV
Part number	1601620	1601635	43906	43916
Maximum continuous air flow (at 0.2 in. w.g.)	139 CFM	183 CFM	177 CFM	157 CFM
Maximum continuous air flow (at 0.4 in. w.g.)	105 CFM	155 CFM	156 CFM	140 CFM
Sensible Recovery Efficiency @ 0°C (64 CFM nominal)	75%	75%	75%	67%
Sensible Recovery Efficiency @ -25°C (64 CFM nominal)	70%	70%	64%	60%
Total Recovery Efficiency @ 35°C (51 CFM nominal)	n/a	n/a	n/a	52%
Dimensions	Height: 25.625 in. (65.087 cm) • Width: 24.4375 in. (62.071 cm) • Depth: 15.125 in. (38.417 cm)			
Pressure taps to balance air flow	Yes	Yes	Yes	Yes
Balancing dampers	Yes	Yes	Yes	Yes
Fan efficacy	1.2 CFM/W	1.2 CFM/W	2.5 CFM/W	2.2 CFM/W
Electrical consumption (low speed)	54 W	54 W	26W	30W
Wall control compatibility	Lite-Touch, Simple-Touch, Bronze, Platinum	Lite-Touch, Simple-Touch, Bronze, Platinum	Deco-Touch, Platinum	Deco-Touch, Platinum
Warranty on parts	5 years	5 years	5 years	5 years
Warranty on core	Limited lifetime	Limited lifetime	Limited lifetime	5 years
 	Yes	Yes	Yes	Yes
	Yes	Yes	Yes	Yes

These specifications are subject to change without notice, please see the specification sheet on www.vanee.ca.

Available at this authorized dealer:



550 Lemire Blvd., Drummondville (Quebec) Canada J2C 7W9
Toll-Free: 1-800-567-3855

www.vanee.ca